

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 2 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Withdrawn) A flexible multilayer packaging material for protecting articles that are sensitive to moisture and oxidizing agents, comprising:
at least one active polymeric barrier layer that binds moisture and oxidizing agents; and
at least one ceramic barrier layer.
2. (Withdrawn) The packaging material according to claim 1, wherein:
the active polymeric barrier layer chemically binds the moisture and oxidizing agents.
3. (Withdrawn) The packaging material according to claim 1, wherein:
the active polymeric barrier layer includes one or more materials from the group consisting of a polymeric matrix with dispersed cyclodextrines, cyclic olefin copolymers and a polymeric matrix with anhydrides.
4. (Withdrawn) The packaging material according to claim 3, wherein:
the ceramic barrier layer includes a material from the group consisting of metal nitrides, metal oxides, metal oxynitrides and combinations thereof.
5. (Withdrawn) The packaging material according to claim 4, wherein:
the at least one active polymeric barrier layer and the at least one ceramic barrier layer are transparent.
6. (Withdrawn) The packaging material according to claim 1, wherein:

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 3 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

the ceramic barrier layer includes one or more materials from the group consisting of metal nitrides, metal oxides and metal oxynitrides.

7. (Withdrawn) The packaging material according to claim 6, wherein:
the metal is aluminum.

8. (Withdrawn) The packaging material of claim 1, wherein:
the ceramic barrier layer includes one or more materials from the group consisting of silicon nitride, silicon oxide and silicon oxynitride.

9. (Withdrawn) The packaging material according to claim 1, wherein:
the at least one active polymeric barrier layer and the at least one ceramic barrier layer are transparent.

10-16. (Canceled)

17. (Currently Amended) An organic electronic device that has one or more components that are sensitive to moisture or oxidizing agents, comprising:
a flexible substrate;
a functional area on the substrate, comprising one or more active organic elements;
a cap encapsulating the functional area; and
a first flexible multilayer packaging material having a first active polymeric barrier layer that binds moisture and oxidizing agents and a ceramic barrier layer, wherein
the first flexible multilayer packaging material protects the functional area; and
the first active polymeric barrier layer includes one or more materials from the group consisting of a polymeric matrix with dispersed cyclodextrines and a polymeric matrix with anhydrides.

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 4 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

18. (Original) The organic electronic device according to claim 17, wherein:
the first flexible multilayer packaging material is arranged between the functional area
and the flexible substrate.
19. (Original) The organic electronic device according to claim 17, wherein the cap
comprises the first flexible multilayer packaging material.
20. (Original) The organic electronic device according to claim 17, wherein the cap
comprises a second flexible multilayer packaging material comprising:
at least one ceramic barrier layer; and
at least one active polymeric barrier layer that binds the moisture and oxidizing agents;
wherein the at least one active polymeric barrier layer of the second flexible multilayer
packaging material includes one or more materials from the group consisting of a polymeric
matrix with dispersed cyclodextrines, a cyclic olefin copolymer and a polymeric matrix with
anhydrides.
21. (Original) The organic electronic device according to claim 17, wherein:
the cap includes one or more materials from the group consisting of polymers, metals and
glass.
22. (Original) The organic electronic device according to claim 17, wherein:
the flexible substrate comprises a polymer.
23. (Original) The organic electronic device according to claim 22, wherein:
the cap comprises a second flexible multilayer packaging material comprising:
at least one active polymeric barrier layer that binds the moisture and oxidizing agents;
and
at least one ceramic barrier layer.

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 5 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

24. (Original) The organic electronic device according to claim 22, wherein:
the cap comprises a second flexible multilayer packaging material comprising:
at least one active polymeric barrier layer that binds the moisture and oxidizing agents;
and
at least one ceramic barrier layer;
wherein the at least one active polymeric barrier layer includes one or more materials
from the group consisting of a polymeric matrix with dispersed cyclodextrines, a cyclic olefin
copolymer and a polymeric matrix with anhydrides.

25. (Original) The organic electronic device according to claim 22, wherein:
the flexible substrate includes a second active polymeric barrier layer.

26. (Original) The organic electronic device according to claim 17, wherein:
the flexible substrate comprises an assembly of active polymeric barrier layers and
ceramic barrier layers.

27. (Original) The organic electronic device according to claim 26, wherein:
the substrate has a first surface and a second surface, the first surface is closer to the
functional area than the second surface and the second surface comprises a ceramic barrier layer.

28. (Currently Amended) The organic electronic device according to claim 17,
wherein:
the ~~functional area~~ one or more active organic elements comprise[[s]] at least one stack
having a first electrically conductive layer, an organic functional layer on the first conductive
layer and a second electrically conductive layer on the organic functional layer; and
the organic functional layer comprises at least one organic electroluminescent layer.

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 6 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

29. (Currently Amended) The organic electronic device according to claim 17, wherein:

the ~~functional area~~ one or more active organic elements include[[s]] at least one stack comprising a first electrically conductive layer, an organic functional layer on the first conductive layer and a second electrically conductive layer on the organic functional layer; and the functional ~~area~~ layer comprises at least one organic radiation detecting layer forming an organic radiation sensor.

30. (Previously Presented) The organic electronic device according to claim 17, wherein the anhydrides are acid anhydrides of organic acids.

31. (Previously Presented) An organic electronic device having one or more components that are sensitive to moisture or oxidizing agents, comprising:

a flexible substrate;
an organic functional area on the substrate, comprising one or more active organic elements;
a cap encapsulating the organic functional area; and
a first flexible multilayer packaging material having a first active polymeric barrier layer that binds moisture and oxidizing agents via chemi- or physisorption and a ceramic barrier layer;
wherein
the first flexible multilayer packaging material protects the organic functional area; and
the substrate comprising an assembly of at least one active polymeric barrier layer and at least one ceramic barrier layer, the substrate having a first surface and a second surface, the first surface being closer to the functional area than the second surface and the second surface comprising a ceramic barrier.

32. (Previously Presented) The organic electronic device according to claim 31, wherein the first active polymeric barrier layer chemically binds moisture and oxidizing agents.

Applicant : Wittmann et al.
Serial No. : 10/816,718
Filed : April 2, 2004
Page : 7 of 8

Attorney's Docket No.: 12406-062001 / P2003,0347 US
E

33. (Currently Amended) An organic electronic device having one or more components that are sensitive to moisture or oxidizing agents, comprising:
- a flexible substrate;
 - an organic functional area on the substrate, comprising one or more active organic elements;
 - a cap encapsulating the organic functional area; and
 - a first flexible multilayer barrier layer that binds moisture and oxidizing agents via chemi- or physisorption and a ceramic barrier layer; wherein
 - the first flexible multilayer packaging material protects the organic functional area; and
 - the substrate comprises an assembly of at least one active polymeric barrier layer and at least two adjacent first and second ceramic barrier layers, the first and second ceramic barrier layers exhibiting different microstructures.
34. (Previously Presented) The device of claim 33, wherein the first and second ceramic barrier layers comprise α -Al₂O₃ and γ -Al₂O₃.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.